

## Realtime T12c

Smallest RFID Professional Access control System



### Specifications

- |   |   |
|---|---|
| » Size                                  | 110 x 70 x 30 (mm)                      |
| » Display                               | 122 x 32 Pixels Serial Blue Backlit LCD |
| » Keypad                                | Light touch 17 Keys                     |
| » Communications                        | RS232/485 USB Cable, USB Disk, TCP/IP   |
| » Door magnetic Sensor/<br>Door Opening | Standard Feature                        |
| » Authentication Modes                  | RFID/EM Card/MIFARE Card/PIN            |
| » Language                              | English                                 |
| » Duress Alarm                          | Standard Feature                        |
| » Max. User                             | 2,000/10,000(Optional)                  |
| » Transaction Records                   | 50,000                                  |
| » Voice Indications                     | Standard Feature                        |
| » Built-in Programmable Alarm           | Standard Feature                        |
| » FAR / FRR                             | 0.0001 % / 0.1%                         |



### Features



## Realtime T600

Card Based Color Display Access Control System



### Specifications

- |                                |   |
|--------------------------------|---|
| » ID Card Capacity             | 10000   |
| » Transaction Capacity         | 100000  |
| » Communication                | TCP/IP, RS232/485, USB Disk, USB Port                               |
| » Access Control Interface for | 3rd Party Electric Lock, Door Sensor, Exit Button, Alarm, Door Bell |
| » Wiegand Signal               | Output & Input  |
| » Optional Functions           | Mifare, HID, Workcode   |
| » Display                      | LCD   |
| » Power Supply                 | 12V DC  |
| » Operating Temperature        | 0°C-45°C  |
| » Operating Humidity           | 20%-80%   |



### Features

