

Realtime T12 Access

Smallest Fingerprint Professional Access control System



Specifications

» Size	110 x 70 x 30 (mm)
» Display	122 x 32 Pixels Serial Blue Backlit LCD
» Keypad	Light touch 16 Keys
» Communications	RS232/485 USB Cable, USB Disk, TCP/IP
» Door magnetic Sensor/Door Opening	Standard Feature
» Authentication Modes	Fingerprint/PIN/RFID EM Card(Optional)
» Language	English
» Duress Alarm	Standard Feature
» Max. Fingerprint Templates	2,000
» Transaction Records	50,000
» Voice Indications	Standard Feature
» Built-in Programmable Alarm	Standard Feature
» FAR / FRR	0.0001 % / 0.1%
» FP Verification Speed	1 sec @ 2000 Templates
» Smart FP Template Update	Standard Feature
» FP Verification Mode	1 : 1 or 1 : N

Features



Realtime T59

Color Screen Professional Access control System



Specifications

» Fingerprint Verified Mode	1 : N : 1 : 1
» Fingerprint Templates	3,000
» Transaction Storage	1,00,000
» Identification Time	≤ 0.8s (3.000 Finger)
» FAR	≤ 0.0001%
» FRR	≤ 0.01%
» Authentication Method	Fingerprint, Password, Card
» Operation Mode	Standalone
» Communication	TCP/IP, USB-Device, USB Disk
» Voice	English
» LCD	2.8 Inch color Display
» LCD Display	User ID, User Name, Fingerprint Image
» Door Open Button	1
» WG Input	WG26/WG34
» WG Output	WG26/WG34
» Access Interface	Reply Output
» Power Supply	DC 12V
» TCP/IP	Yes

Features

